

# Technical Data Sheet

## *55mm Wide Raking Chisel - Carbide Tipped*

### MATERIAL RECOMMENDATIONS

|                        |   |                 |
|------------------------|---|-----------------|
| Heavy Duty Concrete    | ● | ● Very suitable |
| General Concrete       | ● |                 |
| Hard Bricks            | ● |                 |
| Soft Bricks            | ● |                 |
| Lightweight Blocks     | ● |                 |
| Natural Stone          | ● |                 |
| Constructional Granite | ● |                 |
| Limestone              | ● |                 |
| Mortar                 | ● |                 |



### USAGE INFORMATION

Prior to using chisels, please ensure your machine has the 'chisel only' function as they are designed to be used on this function only.

Before using the chisel, please ensure the chuck shank is thoroughly lubricated

For use in heavy duty concrete, general concrete, hard bricks, soft bricks, lightweight block, natural stone, constructional granite, limestone, mortar.

Minimal force should be applied when being used.

After using the product continuously for 10-15 minutes the chisel must be removed from the chuck and allowed to cool at room temperature.

Lubrication must be re-applied before re-using. Products can fail on the shank due to temperature build up of 200°C.

Misuse of the product will decrease the maximum time usage significantly. Shank failure due to temperature build up is not warranted.

